



Series C

BULLETIN

22B

05-05

Pleated Cellulose

Series C cellulose cartridges are designed for general water filtration purposes. They are economical, yet highly effective, at reducing sediment particulates down to nominal 1 micron in size.

The pleated or corrugated media provide increased surface area and strength, which results in extended life. End caps are fused to the cellulose media preventing bypass and forming a gasket sealing area.



Specifications

Type:	Pleated Corrugated Cellulose
Construction:	Resin Impregnated Cellulose Media Vinyl Plastisol End Caps Polypropylene Core Polyethylene Outer Netting (available on request)
Operating Temperature Range:	40°F (4.4°C) to 145°F (63°C)
Micron Rating:	Nominal 1, 5, 20

Dimensions:

2 5/8" diam. X 9 3/4", 10" long
2 5/8" diam. X 19 1/2", 20" long
2 5/8" diam. X 30" long
2 5/8" diam. X 40" long
4 1/2" diam. X 9 3/4" long
4 1/2" diam. X 20" long

Recommended Flow Rates:

5-7 GPM
10-14 GPM
15-21 GPM
20-28 GPM
10-15 GPM
20-30 GPM

Nomenclature

C	5	X	10	BB
Filter Media	Micron Rating		Length	TUBE O.D.
C- Cellulose	1		9 3/4"	All filters are standard 2 5/8" O.D. unless otherwise specified BB - 4 1/2"
	5		10"	
	20		19 1/2"	
			20"	
			30"	
			40"	

Custom sizes available, consult factory.



INCORPORATED

7932 Ajay Drive, Sun Valley, CA 91352
(818) 504-9471 FAX:(818) 768-7590

